



Artikel		Teilung		Innere Breite	Innenglied-breite	Breite zw. AL	Rollen-Ø	Bolzen-Ø	Laschen-höhe	Über-stand	Maß über Bolzen	Gelenk-fläche	Bruch-kraft W	Masse
Nr.	Kurzbez.	p (mm)	p (in)	b ₁ min (mm)	b ₂ max (mm)	b ₃ min (mm)	d ₁ max (mm)	d ₂ max (mm)	g max (mm)	k max (mm)	l ₁ max (mm)	f (cm ²)	F _B min (kN)	m (kg/m)
121980	208 B MA	25,400	1	7,75	11,30	11,43	8,51	4,45	11,80	3,90	17,00	0,50	18,0	0,480
121981	210 B MA	31,750	1 1/4	9,65	13,28	13,40	10,16	5,08	14,70	4,10	19,60	0,67	22,4	0,550
121982	212 B MA	38,100	1 1/2	11,68	15,62	15,75	12,07	5,72	16,10	4,60	22,70	0,89	29,0	0,800
121983	216 B MA	50,800	2	17,02	25,40	25,60	15,88	8,28	21,00	5,40	36,10	2,10	60,0	1,740
121984	220 B MA	63,500	2 1/2	19,56	29,00	29,20	19,05	10,19	28,00	6,10	43,20	2,96	95,0	2,550